Pumps and Dewatering Specialists CR No. 2059002916



مؤسسة سماء المضخات

متخصصون بضخ ونـزح الـمـيـاه رقم السجل التجاري: ۲۹۲٬۰۹۱

PENDENT DRILLHEADS

Pendent Drill heads, Made in UK, with single or twin drive motor with hydraulic drive Drill heads, drill holes up to 1200mm Diameter using Augers. Based on the application suitable Drillrods, DTH-Percussion Rock Hammers, Temporary casings and Buckets for unstable ground can be proposed. The attachment can fit to any Skid Steer, Backhoe Loader, Truck Crane or Excavators.

Basic Specifications:	BD 300-S
Hyd Motors	One
Operating Bar Pressure:	205
Peak Bar Pressure:	310
Max Oil Flow Ipm:	75
*Max Oil Flow with P.V:	260
Operating Torque nm:	2800
Auger Dia's. mm:	100-400



130mm Dia. x 6 metre Depth. One Stroke. Dewatering



130mm Dia. x 7.5 metre Depth One Stroke. DTH Rock Drilling



800mm Dia. x 3 metre Depth. Street-light Foundations

Applications:

Dewatering, Pre Installation of Well Points, Water Wells, Cathodic Protection, Earth Rods, Soil Sampling, Post Holes, Plant Nurseries, Drip Irrigation, Foundation Drilling etc