SKY PUMPS EST.


Pumps and Dewatering Specialists CR No. 2059002916



مؤسسة سماء المضخات

متخصصون بضخ ونزح الهياه رقم السجل التجاري: ٢٠٥٩٠،٢٩١٦

SKY MODEL- DP200M / 8" DEWATERING PUMP



SKY 8" auto priming dewatering pump is the general purpose pump set. Designed for high volume and medium head. Excellent performance in well-point dewatering, sump pumping, transfer and Sewer-bypass.

PUMP SPECIFICATIONS

Performance	Pump Connections	Fuel Tank	Prime mover
 Max Discharge 522 m3/hr Max Head 32 m Max suspended solids handling Size 50 mm 	 Suction 200 mm Discharge 200 mm Miller type couplings Total weight 1300 kg 	 Integrated part of chassis, MS fabricated with four wheel site trailer or skid mounting. 160 Liters Capacity 32 hours + runtime 	 Standard Deutz F4L912 producing 44 kW at 2000 rpm. Standard electric motor 40 kw at 1450 rpm, will be an option.
Priming System	Shaft Sealing	Materials of construction	
 Flood lubricated rotary vacuum pump of minimum displacement 70 CFM incorporating non-return valve. 	 Single side Mechanical Seal spring loaded bellow type with Self lubricated cooling system. 	 Impeller & Stuffing box: Bronze / CF8M Pump Shaft: SS316 Volute Casing: CI / CF8M Vacuum Pump Rotor: SG Priming tank & Discharge head: MS / SS316 Discharge Ball: Polyurethane 	

- The vacuum system allows the pump to prime and re-prime automatically.
- High volume at lower power consumption.
- Solid handling up to 2" (50mm).
- Ceramic coated volute casing.
- Anti Corrosive epoxy zinc phosphate base coating and epoxy scratch resistant anti corrosive ceramic top coat painting for the pump.

Doc- Sky DP200M	Rev. 1	Control NoGP200M	Approved: SS